

Name | Item: Belsoave

Thickness Produktstärke:	ISO 2589	1,3 - 1,5 mm
Colour fastness to artificial light Xenon arc UV-Beständigkeit, Xeno ARC-Labortest	UNI EN ISO 105 B02	≥ 4
Colour fastness to an fro rubbing (Dry – Tocken) Abriebfestigkeit nach Veslic (Wet – Nass)	UNI EN ISO 11640	≥ 4 $\geq 3 / 4$
Sweat Alcaline Solution Alkalischer Schweiß (Sweat – Schweiß)	UNI EN ISO 11641	$\geq 3 / 4$
Finish Adhesion Haftung der Oberflächenbehandlung (N/10 mm)	ISO 1164	≥ 2
Flexing endurance Biegefestigkeit	ISO 5402	> 50.000
Tear strength – Single edge tear Reissfestigkeit Hose	ISO 3377-1	≥ 20
Cold cracking Kältebeständigkeit (-15°C)	EN ISO 17233	Pass Bestanden
Burning behaviour Brandverhalten	FMUSS30 / DIN EN ISO 75 200 / TL 1010	≤ 100
Color Farbe:	Colors available according to RAL color chart. Farben verfügbar gemäß RAL Farbpalette.	

Belsoave is chrom tanned, soft grain leather with a very fine and open-pored structure, made of european bovine hides.

Thickness 1.3-1.5 mm.

Average size of each hide is around 4.5-5.0 sqm.

Finished using water based system.

The extreme softness of the leather enhances its stretch properties.