

<b>Thickness</b> Produktstärke:	ISO 2589	1,2 - 1,5 mm
<b>Colour fastness to artificial light Xenon arc</b> UV-Beständigkeit, Xeno ARC-Labortest	UNI EN ISO 105 B02	>= 5
<b>Colour fastness to an fro rubbing (Dry – Tocken)</b> Abriebfestigkeit nach Veslic (Wet – Nass )	UNI EN ISO 11640	>=4 >= 3 / 4
<b>Sweat Alcaline Solution</b> Alkalischer Schweiß (Sweat – Schweiß)	UNI EN ISO 11641	>= 3 / 4
<b>Finish Adhesion</b> Haftung der Oberflächenbehandlung (N/10 mm)	ISO 1164	>=2
<b>Flexing endurance</b> Biegefestigkeit	ISO 5402	> 50.000
<b>Tear strength – Single edge tear</b> Reissfestigkeit Hose	ISO 3377-1	> = 20
<b>Cold cracking</b> Kältebeständigkeit (-15°C )	EN ISO 17233	Pass Bestanden
<b>Burning behaviour</b> Brandverhalten	FMUSS30 / DIN EN ISO 75 200 / TL 1010	≤ 100
<b>Color</b> Farbe:	Colors available according to RAL color chart. Farben verfügbar gemäß RAL Farbpalette.	

Comfort is embossed corrected grain bovine leather made of european hides.  
Thickness 1.2-1.5 mm.  
Average size of each hide is around 4.5-5.0 sqm.  
Finished using water based system.  
This product has a soft handle with silky matt finish.