

prevent.

PREVENTLEATHER

Quality System ISO 9001:2008
ISO / TS 16949:2009 certified by TÜV

Name | Item: Hunter

Thickness

Produktstärke:

**Colour fastness to artificial light Xenon arc
UV-Beständigkeit, Xeno ARC-Labortest**

**Colour fastness to an fro rubbing (Dry – Trocken)
Abriebfestigkeit nach Veslic (Wet – Nass)**

**Sweat Alkaline Solution
Alkalischer Schweiß (Sweat – Schweiß)**

**Finish Adhesion
Haftung der Oberflächenbehandlung (N/10 mm)**

**Flexing endurance
Biegefestigkeit**

**Tear strength – Single edge tear
Reissfestigkeit Hose**

**Cold cracking
Kältebeständigkeit (-20°C)**

**Burning behaviour
Brandverhalten**

**Color
Farbe:**

ISO 2589 0,8 - 1,0 mm

UNI EN ISO 105 B02 >= 5

UNI EN ISO 11640 >= 4
>= 3 / 4

UNI EN ISO 11641 >= 3 / 4

ISO 1164 >= 2

ISO 5402 > 50.000

ISO 3377-1 > = 20

EN ISO 17233 Pass
Bestanden

FMUSS30 /
DIN EN ISO 75 200 / Pass
TL 1010 Bestanden

Colors available according to RAL color chart.
Farben verfügbar gemäß RAL Farbpalette.

Hunter is chrom tanned, dyed and greased grain bovine leather made of South American hides.

Thickness 1.3-1.5 mm.

Average size of each hide is around 4.5-5.0 sqm.

Finished using water based system.

The grain side is waxed and irregularly roughened in order to retain the used, perished surface look.